

WHEEL

Model "FX 200" Heavy-Duty

A proven performer for trailer loading and unloading. Ideally suited for packaging, shipping and flexible assembly lines. Order optional leg connect brackets to lock units together.

- **Structural Steel Support:** Channel steel spans the entire conveyor width for unequalled strength.
- **1 ¼" Side Plates:** Aluminum alloy with ribbed construction for added durability. Assembled with shoulder bolts.



Model Number	Width	Compacted to Expanded	Conveyor Height	Leg Sets Per Unit	Wheels Per Axle	Unit Weight
FX200-18-12-ST-5	18 in.	3 ft. to 12 ft.	28 ½" to 41 ½"	4	7	215 lbs.
FX200-18-24-ST-5	18 in.	6 ft. to 24 ft.	28 ½" to 41 ½"	7	7	429 lbs.
FX200-24-12-ST-5	24 in.	3 ft. to 12 ft.	28 ½" to 41 ½"	4	9	252 lbs.
FX200-24-24-ST-5	24 in.	6 ft. to 24 ft.	28 ½" to 41 ½"	7	9	504 lbs.

**24 HOUR SHIPMENT SUBJECT TO AVAILABLE STOCK
24 HOUR SHIPMENT NOT GUARANTEED.**

• STANDARD SPECIFICATIONS

WIDTHS—18 in. and 24 in.

FRAME—Flexible and extendible.

LENGTHS—12 ft. and 24 ft.

EXPANSION RATIO—4:1

FLOOR SUPPORTS—Adjustable type 28 ½" to 41 ½".

WHEELS—1.9 in. dia. with ¼ in. bore.

PACKAGE STOP—Folds down when not in use.

CASTERS—Swivel casters with locking brake.

CAPACITY—200 lbs. capacity per linear foot.

• OPTIONAL EQUIPMENT

LEG CONNECT BRACKETS—Connecting two or more conveyors.



LEG CONNECT BRACKETS